

65" 3-in-1 sublimation calender with a 10" diameter drum capable of piece-to-roll, roll-to-roll and piece-to-piece production.



Highlights

- **Fast Warm-up Times** – From ambient temperature to 400°F in under an hour (Infra-Red)
- **Belt Coverage** – Over 72% of the drum is covered, resulting in faster sublimation speeds
- **Production Table Included** – Sports and active wear cut piece production is made easy
- **Automatic Belt Centering** – Dedicated motor and tension system for belt tracking
- **Pre-heat Scheduler** – Program up to 8 different heating cycles based on your production schedule

InPress Calenders- PX Series



**ACTIVE WEAR
PRODUCTION**

**FAST
SPEEDS**

**MAXIMUM
COVERAGE**



HIGHLIGHTS

Maximum Width	
PX-180F	65" (1650 mm)
PX-181F	67" (1700 mm)
Speed	
30 Second Dwell Time	3.9 ft./min. (1.2 m./min.)
40 Second Dwell Time	3 ft./min/ (0.9 m./min)
Heating Type	
PX-180F	Infra-Red
PX-181F	Oil
Drum Diameter	10" (260 mm)
Production Table	Included
Mandrels	3 Unwind & 3 Take-up
Pre-Heat & Cool Down Timers	Yes
Belt Centering	Automatic (Mechanical)
Anti-Ghosting Bar	Included

DIMENSIONS & WEIGHT

Dimensions (WxDxH)	
PX-180F (w/table)	91" x 28" x 55" (91" x 69" x 55")
PX-181F (w/table)	99" x 28" x 55" (99" x 69" x 55")
Weight	
PX-180F	1653 lbs.
PX-181F	2004 lbs.
Crate Dimensions (WxDxH)	
PX-180F	96" x 42" x 67"
PX-181F	106" x 62" x 67"
Crate Weight	
PX-180F	2172 lbs.
PX-181F	2756 lbs.
Power Requirements	
PX-180F	Single Phase 220 Volt 32 Amps
PX-181F	Three Phase 220 Volt 36 Amps

**Warranty
Parts & Labor 1 Year**